





COURONNE **GAMME BÉTON - UNIVERSEL MATÉRIAUX**
S4 | pour tous les usages classiques


Segments soudés laser
jusqu'à 300 mm



Segments diamantés
lisses en pointe
hauteur 11 mm

| RÉFÉRENCE | Ø | RACCORD | SEGMENT | | MACHINE | TYPE DE CAROTTAGE |
|-----------|-----|---------------------|---------------|---|--|---|
| | | | NBR | L x l x h | | |
| S4042N | 42 | 1"1/4 ou 1/2" | 5 | 16 x 3,5 x 11 |  | |
| S4046N | 46 | | 5 | 16 x 3,5 x 11 | | |
| S4052N | 52 | | 5 | 24 x 3,5 x 11 | | |
| S4056N | 56 | | 5 | 24 x 3,5 x 11 | | |
| S4062N | 62 | | 6 | 24 x 3,5 x 11 | | |
| S4066N | 66 | | 6 | 24 x 3,5 x 11 | | |
| S4072N | 72 | | 6 | 24 x 3,5 x 11 | | |
| S4076N | 76 | | 6 | 24 x 3,5 x 11 | | |
| S4082N | 82 | | 7 | 24 x 3,5 x 11 | | |
| S4087N | 87 | | 8 | 24 x 3,5 x 11 | | |
| S4092N | 92 | | 8 | 24 x 3,5 x 11 |  |  |
| S4097N | 97 | | 8 | 24 x 3,5 x 11 | | |
| S4102N | 102 | | 8 | 24 x 4,0 x 11 | | |
| S4107N | 107 | | 9 | 24 x 4,0 x 11 | | |
| S4112N | 112 | | 9 | 24 x 4,0 x 11 | | |
| S4117N | 117 | | 9 | 24 x 4,0 x 11 | | |
| S4122N | 122 | | 9 | 24 x 4,0 x 11 | | |
| S4127N | 127 | | 9 | 24 x 4,0 x 11 | | |
| S4132N | 132 | | 9 | 24 x 4,0 x 11 | | |
| S4137N | 137 | | 9 | 24 x 4,0 x 11 | | |
| S4142N | 142 | 10 | 24 x 4,0 x 11 |  | | |
| S4147N | 147 | 10 | 24 x 4,0 x 11 | | | |
| S4152N | 152 | 11 | 24 x 4,0 x 11 | | | |
| S4157N | 157 | 11 | 24 x 4,0 x 11 | | | |
| S4162N | 162 | 12 | 24 x 4,0 x 11 | | | |
| S4167N | 167 | 12 | 24 x 4,0 x 11 | | | |
| S4172N | 172 | 13 | 24 x 4,0 x 11 | | | |
| S4182N | 182 | 14 | 24 x 4,0 x 11 | | | |
| S4187N | 187 | 14 | 24 x 4,0 x 11 | | | |
| S4192N | 192 | 14 | 24 x 4,0 x 11 | | | |
| S4200N | 200 | 15 | 24 x 4,0 x 11 | | | |
| S4225N | 225 | 16 | 24 x 4,5 x 11 | | | |
| S4252N | 252 | 17 | 24 x 4,5 x 11 | | | |
| S4270N | 270 | 19 | 24 x 4,5 x 11 | | | |
| S4302N | 302 | 20 | 24 x 4,5 x 11 | | | |
| S4320N | 320 | 22 | 24 x 4,5 x 11 | | | |
| S4350N | 350 | 22 | 24 x 4,5 x 11 | | | |

Autres diamètres et longueurs disponibles sur demande

CARACTÉRISTIQUE

- Longueur utile du tube : 450 mm
- Grande capacité de perçage
- Possibilité de resegmentation

MATÉRIAU


béton


 béton
armé

 dalle
gravillon
lavé


brique

MACHINE

 carotteuse
portative


carotteuse