



TEXTO 10



Géotextile de séparation et filtration



Geotextil zum Trennen und Filtrieren



Geotessile di separazione e filtraggio



Geotextile for separation and filtration



Chemin d'accès roulant bitume

Asphaltierte Fahrbahn
Corsia asfaltata
Bituminized lane




Chemin d'accès roulant pavé

Gepflasterte Fahrbahn
Corsia lastricata
Plastered lane







Stockage matériaux

Material Lagerung
Stoccaggio materiale
Material storage




LANDOLT™

TEXTO 10

-  **Géotextile de séparation et filtration**
-  Geotextil zum Trennen und Filtrieren
-  Geotessile di separazione e filtraggio
-  Geotextile for separation and filtration

Chemin d'accès roulant bitume


Asphaltierte Fahrbahn | Corsia asfaltata | Bituminized lane



- Bitume** - Asphalt - Asfalto - Bitumen
- Couche support** - Kofferung - Fondazione - Subgrade
- Couche de forme** - Ausgleichsschicht - Strato di livellamento - Levelling layer
- TEXTO 10**
- Sol** - Grund - Terra - Ground

Chemin d'accès roulant pavé


Gepflasterte Fahrbahn | Corsia lastricata | Plastered lane



- Dalles, pavés** - Pflastersteine - Pietre da pavimentazione - Paving stones
- Sable** - Sand - Sabbia - Sand
- Couche de forme** - Ausgleichsschicht - Strato di livellamento - Levelling layer
- TEXTO 10**










Stockage matériaux

Material Lagerung | Stoccaggio materiale | Material storage



TEXTO 10

Instructions de pose | Gebrauchsanweisung | Istruzioni di posa | Instruction for use

				
 Sens de déroulement	Recouvrement des lés de 20 à 40 cm	Enlever tout élément perforant	Ne pas utiliser en tant qu'étanchéité	Ne pas exposer longtemps au soleil
 Ausrollrichtung	Überlappung der Bahnen 20 bis 40 cm	Entfernen Sie scharfkantige Elemente	Nicht als Dichtungsmaterial geeignet	Nicht zu lange in der Sonne liegen lassen
 Direzione di srotolamento	Sovrapporre di 20-40 cm	Rimuovere elementi a punta	Non idoneo all'impermeabilizzazione	Non esporre a lungo al sole
 Sense of unrolling	Overlapping from 20 to 40 cm	Remove any perforating element	Not suitable as a sealing material	Do not leave too long in the sun